



TYPE: Sepitam-ES424G-QFM

24*10/100/1000Mbps auto-sensing RJ45 ports +
4*Gigabit SFP Fiber ports, Managed Ethernet Switch



Overview

The **Sepitam-ES424G-QFM** is a full gigabit L2+ managed Ethernet fiber switch. It has 4*100/1000Base-X SFP fiber slot ports and 24*10/100/1000Base-T RJ45 ports . Each port can support wire-speed forwarding.

The **Sepitam-ES424G-QFM** has the L2+ full network management, supports IPV4 management, static route full line rate forwarding, complete security protection mechanism, ACL/QOS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as port traffic control, VLAN division, and SNMP through the Web network management mode. It satisfies high-density network application environment and is suitable for medium, large-scale scenes such as hotel, campus, park, shopping mall, scenic spot, hospital, bank to form an economical, efficient and reliable communication network.

Feature

- ◆ **Gigabit access, Gigabit SFP fiber port uplink**
- ◆ All series support “Gigabit Ethernet port and Gigabit SFP port ” combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- ◆ Support non-blocking wire-speed forwarding.
- ◆ Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.
- ◆ **Security**
- ◆ 802.1X authentication.
- ◆ Port isolation, Storm control.
- ◆ IP-MAC-VLAN-Port binding.



- ◆ **Strong business processing capability**
- ◆ IEEE802.1Q VLAN, flexible VLAN division, Voice VLAN and QinQ configuration.
- ◆ QOS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including Equ, SP, WRR & SP+WRR.
- ◆ ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.
- ◆ IGMP V1/V2 and IGMP Snooping.
- ◆ ERPS/STP/RSTP/MSTP.
- ◆ Static and dynamic aggregation.
- ◆ **Stable and reliable**
- ◆ CCC,CE, FCC, RoHS.
- ◆ Low power consumption, galvanized steel casing, The fan active cooling.
- ◆ Self-developed power supply, high redundancy design, providing a long term and stable power output.
- ◆ The user-friendly panel, it can show the device status through the LED indicator of PWR, Link .
- ◆ **Easy operation and maintenance management**
- ◆ Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).
- ◆ HTTPS, SSLV3, and SSHV1/V2.
- ◆ RMON, system log, LLDP, and port traffic statistics.
- ◆ CPU monitoring, memory monitoring, Ping test, and cable diagnose.



Technical Specification

| Model | Sepitam-ES424G-QFM |
|---------------------------|---|
| Interface Characteristics | |
| Fixed Port | 24*10/100/1000Base-T RJ45 ports (Data) 4*100/1000Base-X uplink SFP slot ports (Data) 1 * RS232 console port(115200,N,8,1) |
| Ethernet Port | Port 1-24 support 10/100/1000Base-T(X) auto-sensing, full/half duplex MDI/MDI-X self-adaption |
| Twisted Pair Transmission | 10BASE-T: Cat3,4,5 UTP(≤ 100 meter) 100BASE-TX: Cat5 or later UTP(≤ 100 meter) 1000BASE-T: Cat5e or later UTP(≤ 100 meter) |
| SFP Slot Port | Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC) |
| Optical Cable | Multi mode: 850nm 0 ~ 550M, single mode: 1310nm 0 ~ 40KM, 1550nm 0 ~ 120KM. |
| Chip Parameter | |
| Network Management Type | L2+ |
| Network Protocol | IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3x |



| Forwarding Mode | Store and Forward(Full Wire Speed) |
|---|--|
| Switching Capacity | 192Gbps |
| Forwarding Rate@64byte | 41.7Mpps |
| MAC | 8K |
| Buffer Memory | 4.1M |
| Jumbo Frame | 10K |
| LED Indicator | Power: PWR (yellow), system :SYS (yellow), network ;Link/Act (yellow),Fiber port: L/A(green) |
| Reset Switch | Yes, One-button factory reset |
| Power | |
| Total PWR / Input Voltage | 60W/ (AC100-240V) |
| Power Consumption | Standby<16W, Full load<30W |
| Power Supply | Built-in power supply, AC 100~240V 50-60Hz 0.56A |
| Physical Parameter | |
| Operation TEMP / Humidity | -20~+55°C;5%~90% RH Non condensing |
| Storage TEMP / Humidity | -40~+75°C;5%~95% RH Non condensing |
| Dimension (L*W*H) | 440*290*44.5mm |
| Net /Gross Weight | <3.0kg / <3.8kg |
| Installation | Desktop, 19 inch 1U cabinet |
| Certification & Warranty | |
| Lightning protection / protection level | Lightning protection: 6KV 8/20us; Protection level: IP30 |
| Certification | CCC;CE mark, commercial; CE/LVD EN60950;FCC Part 15 Class B; RoHS; |



Network Management Features

| | |
|------------------|--|
| Interface | <p>IEEE802.3X (Full-duplex)</p> <p>Broadcast storm control based on port speed</p> <p>The speed limit of the message flow in the access port. The minimum particle size is 64Kbps.</p> <p>Port temperature protection setting</p> <p>Port green Ethernet Energy-saving setting</p> |
| Layer 3 Features | <p>L2+ Network management</p> <p>IPV4/IPV6 management</p> <p>L3 soft routing forwarding,</p> <p>Static route, Default route @ 128 pcs, APR @ 1024 pcs</p> |
| VLAN | <p>4K VLAN based on port, IEEE802.1q</p> <p>VLAN based on the protocol</p> <p>VLAN based on MAC</p> <p>Voice VLAN, QinQ configuration</p> <p>Port configuration of Access, Trunk, Hybrid</p> |
| Port Aggregation | <p>LACP, Static aggregation</p> <p>Max 14 aggregation groups and 8 ports per group.</p> |
| Spanning Tree | <p>STP (IEEE802.1d),RSTP (IEEE802.1w),MSTP (IEEE802.1s)</p> |
| Multicast | <p>IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out</p> <p>MLD Snooping v1/v2,Multicast VLAN</p> |
| Port Mirroring | <p>Bidirectional data mirroring based on port</p> |
| QoS | <p>Diff-Serv QoS, Priority Mark/Remark</p> <p>8*Output queues of each port</p> <p>802.1p/DSCP priority mapping</p> <p>Queue Scheduling Algorithm (SP, WRR, SP+WRR)</p> <p>Flow-based Packet Filtering</p> <p>Flow-based Redirection</p> <p>Flow-based Rate Limiting</p> |



| | |
|------------|--|
| ACL | <p>L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc. Port-based Issuing ACL.</p> <p>ACL based on port and VLAN</p> |
| Security | <p>User hierarchical management and password protection SSH 2.0,SSL,Port isolation, message speed limit Broadcast storm control, Backup for host datum IEEE802.1X & MAC address authentication Mac black holes, IP source protection AAA & RADIUS,MAC learning limit ARP inspection, Anti-DoS attack</p> |
| DHCP | <p>DHCP Client, DHCP Snooping, DHCP Server, DHCP Relay</p> |
| Management | <p>Console/AUX Modem/Telnet/SSH2.0 CLI</p> <p>Web Management (HTTPS)</p> <p>Download & Management on FTP, TFTP, Xmodem, SFTP,SNMP V1/V2C/V3</p> <p>One-key recovery</p> <p>NTP, System work log, Ping Test</p> <p>Cable Diagnose, LLDP</p> <p>CPU instant utilization status view</p> <p>NMS - Smart Network Management System Platform (LLDP+SNMP)</p> |
| System | <p>Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later;</p> <p>Category 5 Ethernet network cable</p> <p>TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a</p> |



Technical Specification of Sepitam-ES424G-QFM

شرکت سپیتام



www.Sepitam.com