

TYPE: Sepitam-DH301

Technical Specification of Sepitam-DH931



Description:

Sepitam-DH301 is a high-definition decoder is a professional high-definition AV decoder. It has a HDMI, a CVBS, a VGA output interface and a stereo audio output and it also supports H.265&H.264 decoding format. It receives TS (transport stream) from encoder, and support set the maximum output resolution is 4K(3840*2160@30HZ). This equipment also has high integration and costs low. It can be widely used in various high-definition video systems like multimedia release, digital signage, and signal issuance.

Properties:

- ♦ 1XHDMI output, 1X VGA output, 1XCVBS output, 1X audio output
- Support up to 4K (3840×2160@60hz/30hz) resolution output
- Support to set the cache
- Support 1ch, 4ch, 9ch decoding simultaneously
- Support boot screen customization
- H.265 Baseline Profile decoder
- ♦ H.264 Baseline Profile decoder
- ♦ H.264 Main Profile decoder
- H.264 High Profile decoder
- MJPEG/JPEG Baseline decoder
- MPEG1 Audio Layer 2
- 1000M network interface uses full-duplex mode
- Support HTTP, RTSP, RTMP, RTMPS, SRT, UTP, UDP/RTP protocol
- WEB interface, English and Chinese is optional for configuration interface
- WEB interface management authority
- Support remote management in WAN(WEB)
- Support resolution customized settings
- Support one key to restore the factory configuration
- Support OEM/ODM, secondary development



Specifications:

Output	
Video	1X HDMI, 1X VGA, 1X CVBS, 1X Audio
Output Resolution	3840×2160@30hz 1080P@60/1080P@50/1080P@30 720P@60 720P@50 576P@50 480P@60 1280×1024@60 1280×800@60 1024×768@60 800×600@60 and so on
Decoding	H.265/H.264
Output	1 channel 4K decoding, 4 channels 1080P decoding, 9 channels 720P decoding
Audio	
Decoding format	AAC, MP3
Stereo	Adjustable sound volume
System	
RJ45	100M internet access
Protocol	HTTP, RTSP, RTMP, RTMPS, SRT, UTP, UDP/RTP
Interface	WEB operation interface
Upgrade	Software upgrading through the internet
General Parameters	
Dimension	(width x length x height) 165*85*25mm
Weight	0.21KG per set
Temperature	0~45°c(work), -20~80°c(storage)
Power Supply	Stand-alone: 12V/DC 1A
Power Dissipation	<5W/1 channel



Technical Specification of

Sepitam-DH931

شركت سپيتام



www.Sepitam.com