



## Technical Specification of Sepitam-PS408G-DGDF

**8\*10/100/1000Mbps auto-sensing RJ45 ports + 2\*Gigabit SFP  
+2\*Gigabit RJ45 Uplinks**



### Description:

The Sepitam-PS208G-DGDF is a full gigabit unmanaged PoE fiber switch independently developed by Sepitam. It has 10\*10/100/1000M RJ45 ports and 2\*1000M SFP port slots, Port 1-8 can support IEEE802.3af/at PoE standard, single port PoE power up to 30W, Total power is 130W (at-250W). As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. it can automatically detect and identify the the electrical equipment that meets the standard and supply power to it through the network cable, devices including wireless AP, IP camera, IP telephone and other PoE terminal equipment etc. In addition, it is suitable for networking system of hotel, campus, dormitory and small & medium enterprise etc.

Unmanaged model, plug and play, no configuration, easy to use.

### Properties:

- Full Gigabit access, gigabit TP/SFP port uplink
- ◆ All series supports "gigabit RJ45 port and Gigabit SFP port" combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- ◆ Support non-blocking wire-speed forwarding.
- ◆ Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.
- Intelligent PoE power supply
- ◆ IEEE 802.3af/at PoE standard, without damaging non-PoE devices.
- ◆ 8\*10/100/1000Base-T RJ45 ports, meeting the needs of security monitoring, teleconferencing system, wireless coverage, and other scenarios.
- ◆ Priority system for PoE port, it will supply power to the high priority level port first when the power budget is insufficient and avoid overwork of the device.
- Stable and reliable
- ◆ CCC,CE, FCC, RoHS.
- ◆ Plug and play, no configuration, simple and convenient.
- ◆ Low power consumption, galvanized steel casing, The fan active cooling.
- ◆ Self-developed power supply, high redundancy design, providing a long term and stable PoE power output.
- ◆ The user-friendly panel, it can show the device status through the LED indicator of PWR, Link , L/A, PoE.



### Specifications:

Model	Sepitam-PS208G-DGDF	Sepitam-PS208G-DGDF-at
Interface Characteristics		
Fixed Port	8*10/100/1000Base-T PoE ports (Data /Power) 2*10/100/1000Base-T uplink RJ45 ports (Data) 2*1000Base-X uplink SFP ports (Data)	
Ethernet Port	10/100/1000Base-T,auto-sensing, full/half duplex MDI/MDI-X	
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter)	
SFP Slot Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)	
Optical Cable/ Distance	Multi-mode: 850nm /0 ~ 500M,single mode: 1310nm /0 ~ 40KM, 1550nm/ 0 ~ 120KM.	
Chip Parameter		
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X, IEEE802.3x	
Forwarding Mode	Store and Forward(Full Wire Speed)	
Switching Capacity	24Gbps (Non-blocking)	
Forwarding Rate@64byte	17.86Mpps	
MAC	4K	
Buffer Memory	4M	
Jumbo Frame	9.6K	



LED Indicator	Power: PWR (green), network:Link, Link/Act (yellow),PoE: PoE(green) SFP port: L/A (green), speed : 1000M (green)	
<b>PoE &amp; Power Supply</b>		
PoE Port	Port 1 to 8 IEEE802.3af/at @ POE	
Power Supply Pin	Default 1/2 (+), 3/6 (-)	
Max Power Per Port	30W; IEEE802.3af/at	
Total PWR / Input Voltage	130W (AC100-240V)	250W (AC100-240V)
Power Consumption	Standby:<8W, Full Load:<120W	Standby:<10W, Full Load:<240W
Power Supply	Built-in power supply, AC100~240V 50-60Hz 2.3A	Built-in power supply, AC100~240V 50-60Hz 4.1A
<b>Physical Parameter</b>		
Operation TEMP / Humidity	-20~+55°C;5%~90% RH Non condensing	
Storage TEMP / Humidity	-40~+75°C;5%~95% RH Non condensing	
Dimension (L*W*H)	270*181*44.5mm	
Net /Gross Weight	<1.5kg /<2.0kg	<1.6kg /<2.2kg
Installation	Desktop, wall mounted,19 inch 1U cabinet	
<b>Certification &amp; Warranty</b>		
Lightning protection / protection level	Lightning protection: 4KV 8/20us; Protection level: IP30	
Certification	CCC;CE mark, commercial; CE/LVD EN60950;FCC Part 15 Class B; RoHS	
Warranty	3 years, lifelong maintenance.	



# Technical Specification of Sepitam-PS408G-DGDF

شرکت سپیتام



[www.Sepitam.com](http://www.Sepitam.com)