



TYPE: Sepitam-PI202G-DF

Technical Specification of Sepitam-PI202G-DF

Industrial 2 port 10/100/1000Mbps POE switch and two LC(SFP) fiber ports



Description:

This Industrial equipment can prepare a field that power and data feed from a single point, using Power over Ethernet (PoE) over a single cable. One Two Gigabit Ethernet ports it prepared any 10/100/1000 Mbps link as industry-standard IEEE 802.3af power for every POE standard devices.

This **Sepitam-PI202G-DF** Industrial PoE switch has DIN rail type cabin in order to using in industrial rack and physically passed all CE, RoHS , and FCC standard tests fully. Four Giga bit Power Ports and two 1000MSFP ports in order to connect to Industrial 10Base-T Twisted-pair cable or 100Base-TX Twisted-pair cable and devices such as computer, switch, hub, and server. It can provide one or two remote 1000base-FX cable interface.

Regards to using advanced auto-sensing algorithm the **Sepitam-PI202G-DF** gives power only to IEEE802.3af front-end devices, so don't worry about connecting PoE or non-PoE devices to this feeder. Additionally, this good gives up the power when PoE devices are disconnected. Intelligently, this PoE Switch **Sepitam-PI202G-DF** can recognized automatically PoE demands of devices, speed, duplex, and cable type using Auto Uplink™.

The utilized components in product were rigorous screened, have superior performance in stability, environmental adaptability. A real industrial shell was made by aluminum extrusion, more lighter, stronger, better resistance ability to corrosion and electromagnetic interference, ensure stability and security of Industrial Ethernet Switch, plus standard DIN-35 rail type installation method. Power input also chooses a suitable industry-standard types of power connector, to get more powerful resistance to environment.

**Properties :**

- ◆ Full gigabit design, 2 gigabit ports with Auto Uplink™ , 2 gigabit SFP interfaces.
- ◆ Supports IEEE802.3x flow control for Full-duplex Mode and back pressure for Half-duplex Mode.
- ◆ RJ-45 port supports Auto MDI/MDI-X.
- ◆ Automatic MAC address learning and aging.
- ◆ Auto-Negotiation for Full-duplex Mode and Half-duplex Mode.
- ◆ LED indicators for monitoring power/link/activity and Full-duplex or Half-duplex Mode.
- ◆ Full gigabit ports.
- ◆ Provides both rail type or Wall mounted installation methods.
- ◆ Electromagnetic compatibility of up to 4 grade standard.
- ◆ IP40 protection class.
- ◆ Superior performance, successfully used in industrial field.
- ◆ Power ports supports IEEE802.3af standard PoE power supply.
- ◆ Default PoE power supply type is end-span, mid-span.

Applications:

- ◆ Industrial Field and factories.
- ◆ PLC telecommunication of data industries.
- ◆ Outdoor IP Camera in CCTV monitoring.
- ◆ Outdoor Digital Radio in transmission systems.
- ◆ Outdoor IP telephony in telecom systems.
- ◆ Outdoor Intelligent transportation supervisory system (ITS).
- ◆ Tele-Communication System
- ◆ Security protection system, TV medical treatment
- ◆ Long-distance Multi-media Schooling, Campus monitoring
- ◆ Broadcast television transmission system
- ◆ Wireless AP layout transmission and power supply



Specifications:

Product Name	2GE+2G Full Gigabit Industrial Ethernet Switch
Product Model	Sepitam-PI202G-DF
Interface	2 x 10/100/1000M copper RJ-45 ports, 2 1000M Optical fiber ports
PoE Specification	Supports IEEE802.3af international standard
	PoE Power Output: 15.4W Per port
	PoE total power: 60W
	Power Pin Assignment: 1/2+, 3/6-
Switch Processing Scheme	store-and-forward
Gigabit Optical Interfaces Operating wave length	Single-mode 1310nm or 1550nm, Multi-mode 850nm
Gigabit Optical Interfaces Transmission Distance	Single-mode: 20km, Multi-mode: 550m and long-distance mode can be customized
Performance Specification	Bandwidth: 8Gbps Buffer: 1Mb forwarding Rate: 4.46Mpps@64bytes Address Table: 8K MTBF: 500,000hours
Standards Compliance	IEEE802.3: CSMA/CD IEEE802.3i: 10Base-T IEEE802.3u: 100Base-T IEEE802.3ab: 1000Base-T IEEE802.3z: 1000Base-LX
LED Indicators	Left: LINK/ACT, right: POE
Power	Removable 6 green terminal wiring Power requirements: DC48V1.25A
Product Size	W×D×H: 128x105x47mm
Working Environment	Working Temperature: -40 to 75 degree of centigrade Storage Temperature: -40 to 75 degree of centigrade Working Humidity: 5% to 95% (non-condensing) Storage Humidity: 5% to 95% (non-condensing) Working high: Altitude of 3000 m (10,000ft) Storage high: Altitude of 3000 m (10,000ft)
Radiation	CE mark, commercial FCC Part 15 Class B VCCI Class B EN 55022 , CISPR 22) , Class B
Safety	CE Mark, commercial CE/LVD EN60950



Technical Specification of

Sepitam-PI202G-DF

شرکت سپیتام



www.Sepitam.com