



TYPE: Sepitam-PS208G-DF-ECO

Technical Specification of Sepitam-PS208G-DF-ECO

8*10/100/1000Base-T PoE RJ45 Ports & 2*10/100/1000Base-X SFP Uplink Ports



Description:

Sepitam-PS208G-DF-ECO series is an unmanaged PoE switch, it has 8*10/100/1000Mbps PoE ports and 8*10/100/1000Base-T PoE RJ45 Ports & 2* 10/100/1000Base-X SFP Uplink Ports, Port 1-8 can support IEEE 802.3af/at standard PoE power supply, and the maximum PoE output power is 120W. As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to PoE terminal equipment such as wireless AP, webcam, VoIP phone, video access control intercom, etc. through network cable to meet the network environment that needs high-density PoE power supply. It is suitable for hotels, campuses, factory quarters and small and medium-sized enterprises to form an economy. Efficient network.

Optimized and customized design and affordable pricing, it best fit for SMB or entry-level enterprise solution. It passed the rigorously testing to deliver excellent performance.

Specifications:

| Model | Sepitam-PS208G-DF-ECO |
|-----------------|--|
| Product | 8*10/100/1000Base-T PoE RJ45 Ports & 2* 10/100/1000Base-X SFP Uplink Ports |
| Ports | |
| Network Ports: | 12 |
| PoE Port: | 8*10/100/1000Base-T PoE RJ45 Ports ; Max. 30W Output of Single PoE Port |
| Uplink Port: | 2* 10/100/1000Base-X SFP Uplink Ports |
| Power Indicator | Light on: Powering |
| | Light off: No Power |



Specifications:

| Model | Sepitam-PS208G-DF-ECO |
|-------------------------|--|
| Port 1-10 indicator | Light off: Link is disconnected |
| | Red light on: Powering but data disconnected |
| | Light flash quickly: Data Transmitting |
| Standard | |
| Network Protocol: | IEEE802.3i/802.3u/802.3x/802.3af/802.3ab |
| Performance | |
| Switching Capacity: | 20 Gbps Full duplex |
| Packet Forwarding Rate: | 1.488Mpps/port |
| Forwarding Mode: | Store-and-forward |
| MAC Address Table: | 2K |
| Power Over Ethernet | |
| PoE Standard: | IEEE802.3af, IEEE802.3at |
| PoE Power Supply | 1/2(+) , 3/6(-) |
| Transmission Distance: | RJ45 Port: 0-100m |
| | SFP Port: depended on SFP type |
| PoE Feature | All ports support MDI/MDIX |
| General | |
| Power Source: | Built-in Power Supply |
| | Input: 110-264V AC, 50/60Hz |
| PoE Power Budget: | 120W |
| Power Consumption: | <5W |



Specifications:

| Model | Sepitam-PS208G-DF-ECO |
|----------------------|---|
| ESD | Air discharge: 1.5KV |
| | Contact discharge: 1.5KV |
| Anti-Thunder Level | Common mode: 4KV |
| | Differential mode: 2KV |
| Working Temperature: | -10°C-40°C |
| Humidity: | 10%-95% , non-condensing |
| Storage Temperature: | -40°C-70°C |
| Color | Black |
| Weight: | 1kg (not include input cable & packaging) |
| Dimension (L×W×H): | 202*140*45 mm |



Technical Specification of Sepitam-PS208G-DF-ECO

شرکت سپیتام



www.Sepitam.com